

MATERIAL SAFETY DATA SHEET

SPARKO 440-8078-0 NC BLACK SEALER
SURFACE COATINGS

SPARKO
SURFACE COATINGS

SECTION 1 IDENTIFICATION

Product Code : SPARKO 440-8078-0 NC BLACK SEALER
Dangerous Goods Class : 3
Packaging Type : KG
Use ; For wood coatings.

SECTION 2 HAZARDS CLASSIFICATION

Swallowing : Harmful if swallowed
Skin Absorption : May cause irritation to skin
Inhalation : Trace component and residual monomer vapours may be irritating to the eyes, mucous membrane, respiratory tract, and may produce symptoms of headache and/or nausea in poorly ventilated areas.
Eye Contact : Direct contact may cause eye irritation.

SECTION 3 COMPONENTS

Paint Resin : 24%
Carbon Black : 4%
Di-octyl Phtalate : 2%
Extender Pigment : 27%
Toluene : 9%
Ethyl Acetate : 6%
Isopropyl Alcohol : 5%
N-BAC : 23%

LUZON

**REGIONAL OFFICE
TAGUIG**

1st Ave., Sta. maria Industrial Subd.,
Bagumbayan, Taguig City
Tel #: (02) 506.8519; 837.0710
Fax #: (02) 519.1552

VISAYAS

**HEADQUARTERS
CEBU**

2F SEA Olympus Building, AC Cortes Ave.,
Mandaue City, 6014, Cebu City
Tel #: (032) 421.7817; 421.7262; 421.7863
Fax#: (032) 346.1817; 421.7877

MINDANAO

**REGIONAL OFFICE
DAVAO**

Unit A16 J. King Warehouse Complex
Km. 3 Maa Road, Davao City 8000
Tel # (082) 244.1206
Fax #: (082) 285.2886

SECTION 4 PHYSICAL DATA AND CHEMICAL PROPERTIES

Appearance	:	Black
Form	:	Liquid
Odor	:	Smell of Solvent
Boiling Point	:	Ca.117°C (760 mm Hg)
Specific gravity	:	1.0-1.04
Flash Point	:	28°C
Solubility in Water	:	Insoluble
Flammable Limits of Volatiles	:	1.0 – 10.8%

SECTION 5 HEALTH & SAFETY AND HAZARD INFORMATION

HEALTH & SAFETY

Proper use of this product will not result in occupational hazards.

5.1 HANDLING & STORAGE:

EYE PROTECTION:	Chemical type goggles is recommended. Eyewash stations in the work area are also recommended
RESPIRATORY PROTECTION:	Proper respiratory equipment must be worn at all times when handling or using this product.
SKIN PROTECTION:	Proper protective gloves should be worn. Proper body protective gear is recommended.
VENTILATION:	Proper ventilation is required. Other equipment used must be resistant to explosion.
STORAGE:	Material must be stored in a cool dry area.

5.2 EMERGENCY AND FIRST AID:

EYE CONTACT:	Thorough flushing with water for at least 15 minutes. Get immediate medical assistance.
SKIN CONTACT:	Wash areas of contact repeatedly with soap and water. Seek immediate medical assistance if irritation persists.
INGESTION:	NEVER INDUCE VOMITING. Seek immediate medical assistance.

LUZON

REGIONAL OFFICE TAGUIG

1st Ave., Sta. maria Industrial Subd.,
Bagumbayan, Taguig City
Tel #: (02) 506.8519; 837.0710
Fax #: (02) 519.1552

VISAYAS

HEADQUARTERS CEBU

2F SEA Olympus Building, AC Cortes Ave.,
Mandaue City, 6014, Cebu City
Tel #: (032) 421.7817; 421.7262; 421.7863
Fax#: (032) 346.1817; 421.7877

MINDANAO

REGIONAL OFFICE DAVAO

Unit A16 J. King Warehouse Complex
Km. 3 Maa Road, Davao City 8000
Tel # (082) 244.1206
Fax #: (082) 285.2886

INHALATION: Prevent further exposure. Seek immediate medical assistance if dizziness, nausea or unconsciousness is experienced.

IMPORTANT!: The product, if inhaled/breathed into the lungs, may cause chemical pneumonitis. Treat as required.

5.3 FIRE AND EXPLOSION HAZARD:

Fire Extinguishing: Dry Chemicals, Carbon Dioxide, Foam and Water Fog
Special fire fighting equipment: Self-contained breathing apparatus should be used by Fire fighters.

5.4 SPILLS OR LEAKS:

Small spills can be washed off with large amounts of water; spills of a larger scale must be PROPERLY DISPOSED. The product may be toxic to aquatic lives; DO NOT dispose in natural bodies of water. Proper protective equipment should be worn.

SECTION 6 WASTE DISPOSAL

Make sure that all ignition sources are not present. Use fire retardant treated sawdust, earth, etc. to absorb the material. Place in proper disposal receptacles. Waste disposal facilities that are in accordance with local laws and regulations must be employed to dispose of the material.

The data and information contained in this Material Safety Data Sheet is provided to the best of our knowledge and ability on existing hazards, properties and handling of this product as recommended. It is recommended that the user tests the product according to its purpose. The user is responsible for the proper, safe and lawful use of this product. The information contained in this MSDS is subject to change without further notice. ©20

LUZON

REGIONAL OFFICE TAGUIG

1st Ave., Sta. maria Industrial Subd.,
Bagumbayan, Taguig City
Tel #: (02) 506.8519; 837.0710
Fax #: (02) 519.1552

VISAYAS

HEADQUARTERS CEBU

2F SEA Olympus Building, AC Cortes Ave.,
Mandaue City, 6014, Cebu City
Tel #: (032) 421.7817; 421.7262; 421.7863
Fax #: (032) 346.1817; 421.7877

MINDANAO

REGIONAL OFFICE DAVAO

Unit A16 J. King Warehouse Complex
Km. 3 Maa Road, Davao City 8000
Tel # (082) 244.1206
Fax #: (082) 285.2886