



## TECHNICAL DATA SHEET

### SPARKO 440-V-8030-0 NC ANTI-YELLOWING WHITE SEALER

#### CHEMICAL IDENTIFICATION

Product Description : SPARKO 440-V-8030-0 NC ANTI-YELLOWING WHITE SEALER

Product Code : 440-V-8030-0

#### SPECIFICATION

Specific Gravity : 1.33 +/- 0.05KG/Liter  
Solids by Weight : 67 +/- 2%  
Viscosity : 90-98 KU  
Color : White  
Drying Time : Dry-Hand: 10 to 15mins.

#### VOLATILE ORGANIC COMPOUNDS

Coating Density : 10.5 lb/gal 1260g/l  
Percent Non-Volatile : By wt: 55 % - 5.78 Lb/gal By Vol 43.65 % - 550g/l  
Organic Volatiles : By wt: 45 % - 4.73 Lb/gal By Vol 35.71 % - 450g/l  
VOC Content : 4.73 Lb/gal 567g/L

#### APPLICATION RECOMMENDATIONS

Agitation : Agitate well before and during use  
Mixing Ratio : 1:2, 440-V-8030-0: 601 Sparko Lacquer Thinner  
Curing Requirement : N/A  
Application Method : Spray  
Storage : Store indoor away from heat or naked flame, under normal conditions of temperature and humidity

#### HEALTH AND SAFETY

Proper personal protective equipment must be worn while using this product. This product should also be used in a well-ventilated spray booth. Avoid breathing in or smelling this product at all times. Please refer to our Material Safety Data Sheets (MSDS) for more health and safety details.

*The information contained in this product specification sheet has been provided based on our laboratory results. The type, quality and characteristics of substrates used, the environment of the end-user, individual systems or processes employed by the end-user and other conditions are elements which are beyond our control and we therefore recommend that the end-user test the product for the specific application, substrate required under the end-users environment and other working conditions. Sparko will not be held liable for damages to the improper use of our products. All information stated above are subject to change without prior notice. ©20*

#### LUZON

##### REGIONAL OFFICE

##### TAGUIG

1st Ave., Sta. maria Industrial Subd.,  
Bagumbayan, Taguig City  
Tel #: (02) 506.8519; 837.0710  
Fax #: (02) 519.1552

#### VISAYAS

##### HEADQUARTERS

##### CEBU

2F SEA Olympus Building, AC Cortes Ave.,  
Mandaue City, 6014, Cebu City  
Tel #: (032) 421.7817; 421.7262; 421.7863  
Fax#: (032) 346.1817; 421.7877

#### MINDANAO

##### REGIONAL OFFICE

##### DAVAO

Unit A16 J. King Warehouse Complex  
Km. 3 Maa Road, Davao City 8000  
Tel # (082) 244.1206  
Fax #: (082) 285.2886